

The Next Generation Continuous Infusion Syringe Pump System

Continuous NE-1000X- \$1720
Model: DUAL-NE-1000X

Eliminates Flow Rate Pauses & Drop-Offs!

Eliminates the problem of flow rate drop-off found in Push-Pull syringe pumps. In these Push-Pull systems, one pump is refilling while the other infuses and then they switch directions. That switch of directions causes a pause or drop in flow. The Continuous NE-1000X's continuous pumping mode eliminates the flow rate drop offs and pauses.

How it Works:

- Refilling pump refills the syringe at a faster rate than the infusing pump, giving it time to prime the syringe.
- Refilling pump pauses and waits for the infusing pump to empty.
- When the pumps switch directions, the refilled pump is primed and starts infusing at the set rate immediately.

Features:

- Two NE-1000X Family of Syringe Pumps connected together via a Dual Pump Sync Cable
- Continuous Pumping Mode provides a precise continuous flow without any drop-offs or pauses.
- Programmable infusion, refill and prime rates and syringe overlap and prime volumes
- Flexibility for the pumps to perform either continuous flow, emulsification, or independently at any time



NE-1000X Family of Syringe Pumps features:

- Built for Automation
- Operates stand-alone or from a computer
- Infuses and withdraws
- Applications range from simple infusions to complex pumping programs
- Programmable preset protocols
- Program up to 41 pumping phases that change pumping rates, set dispensing volumes, insert pauses, control and respond to external signals, sound the buzzer
- RS-232 and TTL logic control interfaces
- Network, control, and monitor up to 100 pumps with one computer
- Gradient ramping of flow rates
- Worldwide power supplies available
- Motor stall detection
- Non-volatile memory of all parameters and programming
- Upgradeable to 340 pumping phases program memory with the X2 Upgrade
- Plus many, many more features!!!
- Dispensing accuracy of +/-1%
- Unlimited lifetime technical support
- Two year warranty

Dual Pump Plumbing Kit



For use with our continuous infusion system or dual infusion system. Provides a dual check valve for two syringes, withdraw will pull fluid from a reservoir and infusion will output into a separate line. The kit is pre-assembled, all you need to do is plug in the syringes. Each dual check valve uses 6" of 1/8" tubing to connect to a Y connector, one for reservoir and one for output; each Y-connector has 5' of tubing to make connections to your application. Two 60cc Terumo syringes are included.

Individual parts are also available.
Model: P-DKIT

Not For Clinical Use On Humans



Model: NE-1000 Syringe Pump

Maximum and Minimum Flow Rates

Manufacturer	Syringe (cc)	Inside Diameter (mm)	Maximum Rate (mL/hr)	Minimum Rate (µL/hr)	Maximum Rate (mL/min)
B-D	1	4.699	53.07	0.73	0.884
	3	8.585	177.1	2.434	2.952
	5	11.99	345.5	4.748	5.758
	10	14.43	500.4	6.876	8.341
	20	19.05	872.2	11.99	14.53
	30	21.59	1120	15.4	18.67
	60	26.59	1699	23.35	28.32
Monoject	1	5.74	79.18	1.088	1.319
	3	8.941	192.1	2.64	3.202
	6	12.7	387.6	5.326	6.46
	12	15.72	593.9	8.161	9.899
	20	20.12	972.9	13.37	16.21
	35	23.52	1329	18.27	22.15
	60	26.64	1705	23.44	28.42
	140	38	3470	47.69	57.84
Terumo	1	4.7	53.09	0.73	0.884
	3	8.95	192.5	2.646	3.208
	5	13	406.1	5.581	6.769
	10	15.8	600	8.244	10
	20	20.15	975.8	13.41	16.26
	30	23.1	1282	17.63	21.37
	60	29.7	2120	29.13	35.33
Air-Tite	1	6.7	107.8	1.483	1.798
	2	8.91	190.8	2.622	3.18
	3	9.06	197.2	2.711	3.288
	5	11.75	331.8	4.559	5.53
	10	14.67	517.2	7.107	8.62
	20	19.62	925.2	12.72	15.42
	30	22.69	1237	17.01	20.62
	50	26.96	1746	24.01	29.11
Steel Syringes	1	9.538	218.6	3.005	3.644
	3	9.538	218.6	3.005	3.644
	5	12.7	387.6	5.326	6.46
	8	9.538	218.6	3.005	3.644
	20	19.13	879.5	12.09	14.65
	50	28.6	1965	27.01	32.76

	Syringe (µL)	Inside Diameter (mm)	Maximum Rate (µL/hr)	Minimum Rate (µL/hr)	Syringe (mL)	Inside Diameter (mm)	Maximum Rate (mL/hr)	Minimum Rate (µL/hr)
SGE	5	0.343	282.7	0.004	.25	2.303	12.74	0.176
	10	0.485	565.3	0.008	.5	3.257	25.49	0.351
	25	0.728	1273	0.018	1	4.606	50.99	0.701
	50	1.03	2549	0.036	2.5	7.284	127.5	1.752
	100	0.457	5102	0.071	5	10.3	254.9	3.504
Hamilton Microliter	0.5	0.103	25.49	0.001	10	14.57	510.2	7.01
	1	0.146	51.23	0.001	25	23.03	1274	17.52
	2	0.206	101.9	0.002	50	27.5	1817	24.98
	5	0.326	255.4	0.004	100	34.99	2942	40.43

Not For Clinical Use On Humans


SyringePump.com
Clever Pumps, Priced Right!

Pump Systems Inc.
 SyringePump.com
 New Era Pump Systems, Inc.
 138 Toledo St. • Farmingdale, NY 11735 • 631-249-1392



Model NE-1000 Specifications

Mechanical & Electrical

Syringe sizes:	Up to 60 mL (140 mL partially filled)
Number of syringes:	1
Motor type:	Step motor
Motor steps per revolution:	400
Microstepping:	1/8 to 1/2 depending on motor speed
Advance per step:	0.2126 μ M to 0.8504 μ M depending on motor speed
Motor to drive screw ratio:	15/28
Drive screw pitch:	20 revolutions/”
DC connector:	2.1 mm, center positive
Voltage at DC connector:	12V DC at full load
Amperage:	750 mA at full load
Power supply type:	Unregulated linear external wall adapter, country and power source specific
Power supply output rating:	12V DC @ 800 mA
Dimensions:	8 3/4” x 5 3/4” x 4 1/2” High (22.86 cm x 14.605 cm x 11.43 cm)
Weight:	3.6 lbs. (1.63 kg)
Allen Wrench	3/32 Hex

Operational

Maximum speed:	5.1005 cm/min
Minimum speed:	0.004205 cm/hr
Maximum pumping rate:	1699 ml/hr with a B-D 60 cc syringe
Minimum pumping rate:	0.73 μ l/hr with a B-D 1 cc syringe
Maximum force:	35 lbs. at minimum speed, 18 lbs. at maximum speed
Number of Program Phases:	41
RS-232 pump network:	100 pumps maximum
RS-232 selectable baud rates:	300, 1200, 2400, 9600, 19200
Syringe inside diameter range:	0.100 to 50.00 mm

Custom Applications

For specialized and OEM applications, contact your dealer or New Era Pump Systems Inc. Custom modifications can be made to the mechanics or the firmware.

Not For Clinical Use On Humans



SyringePump.com
Clever Pumps, Priced Right!

New Era Pump Systems, Inc.
138 Toledo St. • Farmingdale, NY 11735 • 631-249-1392

